

USL



Solar

Photovoltaic

Modules

USP37 / USP40 / USP45

USL provides cost-effective photovoltaic power for general use, operating DC directly or, in an inverter-equipped system, AC loads. The 36 cells in series provides 37W, 40W & 45Watts of maximum power, it is used primarily in utility grid-supplemental systems, telecommunications, remote villages and clinics, pumping and load-based aids to navigation.

M5

&

P5

S

E

R

I

E

S



*M5 Series:
Monocrystalline modules*

*P5 Series:
Polycrystalline Modules*

Electrical and Mechanical Data


Model	USP37	USP40	USP45
Maximum power (Pmax)	37 Wp	40 Wp	45 Wp
Open Circuit Voltage (Voc)	21.5 V	21.5 V	21.8 V
Maximum power point voltage (Vmpp)	17.1 V	17.1 V	17.3 V
Short circuit current (Isc)	2.43 A	2.62 A	2.91 A
Maximum power point current (Impp)	2.17 A	2.34 A	2.60 A
Tolerance	±10%	±10%	±10%
Cell Size (mm)	62.5 x 125	62.5 x 125	62.5 x 125
No. of cells	36	36	36
Dimensions (mm) ± 1	635 x 550 x 38	635 x 550 x 38	635 x 550 x 38
Maximum system voltage	600	600	600
Temperature co-efficient	NOCT (°C)45	NOCT (°C)45	NOCT (°C)45
$\frac{\partial V_{oc}}{\partial T}$ (mV/°C)	- 105	- 105	- 105
$\frac{\partial I_{sc}}{\partial T}$ (mA/°C)	- 0.32	- 0.32	- 0.32
$\frac{\partial P_{max}}{\partial T}$ (%/°C)	- 0.45	- 0.45	- 0.45
Weight (kgs)	4.2	4.2	4.2

Standard Test Condition : Irradiance 1,000 W/sq.m, Temperature 25deg C Air mass 1.5 spectrum)

Proven Materials and Construction

USL experience shows in every aspect of this module's construction and materials

- Anodized aluminum frame offers required strength and allows for quick and easy installation on standard array structures.
- 36 Crystalline silicon solar cells in series.
- Modules are laminated in toughened low iron content PV grade glass – Ethyl Vinyl Acetate films – PV module back sheet.
- Optimized lamination process parameters ensure a stable laminate. Junction Box with PG Cable glands are standard in all modules.
- Each module is flash tested in a Sun simulator to ensure conformity to specification.



Udhaya Semiconductors Limited

Coimbatore: 641 062. INDIA.

Phone: +91 422 2627003 Fax : +91 422 2628504

Email: info @ uslsolar.com; Website : www.uslsolar.com